

TAKE OFF DISTANCE

C150M 726 kp

0-FLAPS

	STD	ACT
QNH	1013,25	1013
ALT		1500
TEMP	12,00	31

PA **1500**
 DA **3657**
 FAKTOR 0,60

T/O Distance: --> **518**
 (ohne Wind) -----> **543**
 Mittelw. **530**

0° FÜR C150M in m

PA/FT	RUN	DIST	FAKT
0	206	389	572
	240	443	646
2500	262	479	696
	303	545	787
5000	331	589	847
	381	682	983
7500	415	744	1073

10° FÜR C150M in m

PA/FT	RUN	DIST	FAKT
0	218	411	604
	253	468	683
2500	277	506	735
	320	575	830
5000	348	621	894
	401	718	1035
7500	437	783	1129

20° FÜR C150M in m

PA/FT	RUN	DIST	FAKT
0	235	433	631
	269	493	717
2500	292	533	774
	337	605	873
5000	367	653	939
	422	754	1087
7500	459	822	1185

30° FÜR C150M in m

PA/FT	RUN	DIST	FAKT
0	242	455	668
-->	280	518	756
2500	306	560	814
	353	635	917
5000	385	685	985
	443	791	1140
7500	481	862	1243

40° FÜR C150M in m

PA/FT	RUN	DIST	FAKT
0	254	478	702
----->	294	543	792
2500	320	586	852
	370	664	958
5000	403	716	1029
	463	827	1191
7500	503	901	1299