

TAKE OFF DISTANCE			
C172RG in ft	2500lbs		
	Flaps	UP	
	STD		ACT
QNH	1013,25		1013
ALT		ELEV	1860
TEMP	11,28		11
PA			1860
DA	1860		
FAKTOR			0,86
T/O Distance:	-->		2480
(ohne Wind)	----->		2651
	Mittelw.		2566
0°			2500lbs
PA/FT	RUN	DIST	EDMJ
0	835	1400	1965
	900	1508	2116
1000	910	1525	2140
	983	1650	2316
2000	995	1670	2345
	1077	1812	2547
3000	1090	1835	2580
	1180	1990	2799
4000	1195	2015	2835
10°			2500lbs
PA/FT	RUN	DIST	EDMJ
0	895	1495	2095
	964	1615	2267
1000	975	1635	2295
-->	1057	1768	2480
2000	1070	1790	2510
	1156	1941	2725
3000	1170	1965	2760
	1265	2137	3009
4000	1280	2165	3050
20°			2500lbs
PA/FT	RUN	DIST	EDMJ
0	960	1595	2230
	1033	1724	2415
1000	1045	1745	2445
----->	1131	1891	2651
2000	1145	1915	2685
	1240	2078	2917
3000	1255	2105	2955
	1358	2294	3230
4000	1375	2325	3275
30°			2500lbs

<i>PA/FT</i>	<i>RUN</i>	<i>DIST</i>	<i>EDMJ</i>
0	1025	1705	2385
	1107	1843	2579
1000	1120	1865	2610
	1210	2024	2838
2000	1225	2050	2875
	1328	2231	3133
3000	1345	2260	3175
	1457	2466	3476
4000	1475	2500	3525
40°			2500lbs
<i>PA/FT</i>	<i>RUN</i>	<i>DIST</i>	<i>EDMJ</i>
0	1100	1820	2540
	1186	1971	2755
1000	1200	1995	2790
	1299	2167	3035
2000	1315	2195	3075
	1423	2389	3355
3000	1440	2420	3400
	1560	2648	3735
4000	1580	2685	3790